



3051 DOUBLE COATED TISSUE TAPE WITH SOLVENT ACRYLIC ADHESIVE

MATERIAL SPECIFICATION SHEET

Product Properties:

Provides good holding power and has a good performance at elevated temperatures

Specifications:

ROHS Compliant

Storage & Ageing:

1 year shelf-life whilst stored in original packaging at ambient room temperature. Keep out of direct sunlight.

TECHNICAL DETAILS	TYPICAL VALUE	UNITS
Carrier Type	Tissue	
Adhesive Type	Acrylic	
Colour	Translucent	
Liner Type	Paper silicone coated white	
Total Thickness	0.11	mm
Adhesion on Stainless Steel	14	N/25mm
Service Temperature	-30 to +130	°C
Application Temperature	+8 to +38	°C

Additional Technical Properties:

Rolling ball test 120mm

Static shear test @ 23°C – 800 minutes according GB/T2792-1998

Static shear test @ 80°C – 15 minutes according GB/T4851-1998



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company