

ANSI – ASME- B16.21

N-Bore		Full Face (mm)					ASME B16.21	IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	CLASS 150	OD	ID
0.5	15	89	21	4	16	60		48	21
0.75	20	95	27	4	16	70		57	27
1	25	108	33	4	16	79		67	33
1.25	32	117	42	4	16	89		76	42
1.5	40	127	48	4	16	98		86	48
2	50	152	60	4	19	121		105	60
2.5	65	178	73	4	19	140		124	73
3	80	191	89	4	19	152		137	89
3.5	90	216	102	8	19	178		162	102
4	100	229	114	8	19	191		175	114
5	125	254	141	8	22	216		197	141
6	150	279	168	8	22	241		222	168
8	200	343	219	8	25	298		279	219
10	250	406	273	12	25	362		340	273
12	300	483	324	12	29	432		410	324
14	350	533	356	12	29	476		451	356
16	400	597	406	16	32	540		514	406
18	450	635	457	16	32	578		549	457
20	500	699	508	20	32	635		606	508
24	600	813	610	20	35	749		718	610



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company