

ANSI – ASME- B16.21

N-Bore		Full Face (mm)					ASME B16.21	IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	CLASS 1500	OD	ID
0.5	15	121	21	4	22	83		64	21
0.75	20	130	27	4	22	89		70	27
1	25	149	33	4	25	102		80	33
1.25	32	159	42	4	25	111		89	42
1.5	40	178	48	4	28	124		99	48
2	50	216	60	8	25	165		143	60
2.5	65	244	73	8	28	191		165	73
3	80	241	89	8	25	203		181	89
4	100	311	114	8	32	235		207	114
5	125	375	141	8	35	279		245	141
6	150	394	168	12	32	318		289	168
8	200	483	219	12	38	394		359	219
10	250	584	273	16	38	470		435	273
12	300	673	324	20	38	533		499	324
14	350	749	356	20	41	559		521	356
16	400	826	406	20	44	616		575	406
18	450	914	457	20	51	686		638	457
20	500	984	508	20	54	749		699	508
24	600	1168	610	20	67	902		838	610



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company