

## ANSI – ASME- B16.21

N-Bore		Full Face (mm)					ASME B16.21	IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	CLASS 300	OD	ID
0.5	15	95	21	4	16	67		54	21
0.75	20	117	27	4	19	83		67	27
1	25	124	33	4	19	89		73	33
1.25	32	133	42	4	19	98		83	42
1.5	40	156	48	4	22	114		95	48
2	50	165	60	8	19	127		111	60
2.5	65	191	73	8	22	149		130	73
3	80	210	89	8	22	168		149	89
1	90	229	102	8	22	184		165	102
4	100	254	114	8	22	200		181	114
5	125	279	141	8	22	235		216	141
6	150	318	168	12	22	270		251	168
8	200	381	219	12	29	330		308	219
10	250	445	273	16	29	387		362	273
12	300	521	324	16	25	451		422	324
14	350	584	356	20	32	514		486	356
16	400	648	406	20	35	572		540	406
18	450	711	457	24	35	629		597	457
20	500	775	508	24	35	686		654	508
24	600	914	610	24	41	813		775	610



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company