

ANSI – ASME- B16.47 A

N-Bore		Full Face (mm)					ASME B16.47 A	IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	CLASS 150	OD	ID
22	550	749	559	20	35	692		660	559
26	650	870	660	24	35	806		775	660
28	700	927	711	28	35	864		832	711
30	750	984	762	28	35	914		883	762
32	800	1060	813	28	41	978		940	813
34	850	1111	864	32	41	1029		991	864
36	900	1168	914	32	41	1086		1048	914
38	950	1238	965	32	41	1149		1111	965
40	1000	1289	1016	36	41	1200		1162	1016
42	1050	1346	1067	36	41	1257		1219	1067
44	1110	1403	1118	40	41	1314		1276	1118
46	1150	1454	1168	40	41	1365		1327	1168
48	1200	1511	1219	44	41	1422		1384	1219
50	1250	1568	1270	44	48	1480		1435	1270
52	1300	1623	1321	44	48	1537		1492	1321
54	1350	1683	1372	44	48	1594		1549	1372
56	1400	1746	1422	48	48	1651		1607	1422
58	1450	1803	1473	48	48	1708		1664	1473
60	1500	1854	1524	52	48	1759		1715	1524



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company