

## ANSI – ASME- B16.47 A

N-Bore		Full Face (mm)					ASME B16.47 A	IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	CLASS 300	OD	ID
22	550	838	559	24	41	743		705	559
26	650	972	660	28	44	876		835	660
28	700	1035	711	28	44	940		899	711
30	750	1092	762	28	48	997		953	762
32	800	1149	813	28	51	1054		1007	813
34	850	1207	864	28	51	1105		1057	864
36	900	1270	914	32	54	1168		1118	914
38	950	1168	965	32	41	1092		1054	965
40	1000	1207	1016	32	44	1156		1115	1016
42	1050	1289	1067	32	44	1207		1165	1067
44	1110	1365	1118	32	48	1264		1219	1118
46	1150	1416	1168	28	51	1321		1273	1168
48	1200	1467	1219	32	51	1372		1324	1219
50	1250	1581	1270	32	54	1429		1378	1270
52	1300	1657	1321	32	54	1480		1429	1321
54	1350	1683	1372	28	60	1579		1492	1372
56	1400	1708	1422	28	60	1600		1543	1422
58	1450	1759	1473	32	60	1651		1594	1473
60	1500	1810	1524	32	60	1702		1645	1524



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company