

BS10 STANDARD SIZING

TABLE K

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
0.5	15	114	21	4	18	83	65	21
0.75	20	114	27	4	18	83	65	27
1	25	127	34	4	18	95	78	34
1.25	32	133	43	4	18	98	81	43
1.5	40	152	48	4	22	114	92	48
2	50	165	60	8	18	127	110	60
2.5	65	184	76	8	22	146	124	76
3	80	203	89	8	22	165	143	89
3.5	90	229	102	8	25	184	159	102
4	100	241	114	8	25	197	171	114
5	125	279	140	12	25	235	210	140
6	150	305	168	12	25	260	234	168
7	0	343	191	12	29	292	264	191
8	200	368	216	12	29	318	289	216
9	230	406	241	16	29	356	327	241
10	250	432	270	16	29	381	352	270
12	300	489	321	16	29	432	400	321
13	330	546	346	16	35	483	448	346
14	350	572	371	16	35	508	473	371
15	380	603	397	20	35	540	505	397



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company