



NEOPRENE TUBING

MATERIAL SPECIFICATION SHEET

Suitable for fuel applications abrasion resistant, ageing resistant.

Tube	Extruded Smooth Neoprene Rubber Tube
Colour	Black
Temperature Range	-30°C to +100°C
Specification	ASTM D 2000.BC510
Hardness	70 +5/-0
Specific Gravity	1.2
Tensile Minimum	10 MPa
Elongation at break	>350%
Compression Set	<80% (22hrs @100°C)
Heat Ageing Test	770 hrs @100°C

I.D. (mm)	O.D. (mm)	WEIGHT (kg/m)	MAX COIL (m)
3	5	0.04	100
5	8	0.04	100
6	9	0.05	100
8	12	0.07	100
10	14	0.10	100
12.5	17	0.20	100
16	22.5	0.24	100
20	26.5	0.28	100
25	31.5	0.34	100



ISO 9001:2015 Q93057 ISO 14001:2015 EMS 505718

The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company