

# PN10

N-Bore		Full Face (mm)					IBC (mm)	
in	mm	OD	ID	Holes	Dia.	P.C.D.	OD	ID
	10	90	18	4	14	60	45	18
0.5	15	95	22	4	14	65	50	22
0.8	20	105	28	4	14	75	60	28
1	25	115	35	4	14	85	70	35
1.3	32	140	43	4	18	100	82	43
1.5	40	150	49	4	18	110	92	49
2	50	165	61	4	18	125	107	61
2.5	65	185	77	8	18	145	127	77
3	80	200	90	8	18	160	142	90
4	100	220	115	8	18	180	162	115
5	125	250	141	8	18	210	192	141
6	150	285	169	8	22	240	218	169
8	200	340	220	8	22	295	273	220
10	250	395	274	12	22	350	328	274
12	300	445	325	12	22	400	378	325
14	350	505	356	16	22	460	438	356
16	400	565	407	16	26	515	489	407
18	450	615	458	20	26	565	539	458
20	500	670	508	20	26	620	594	508
24	600	780	610	20	30	725	695	610
28	700	895	712	24	30	840	810	712
32	800	1015	813	24	33	950	917	813
36	900	1115	915	28	33	1050	1017	915
40	1000	1230	1016	28	36	1160	1124	1016
	1100	1340	1120	32	39	1270	1231	1120
48	1200	1455	1220	32	39	1380	1341	1220
56	1400	1675	1420	36	42	1590	1548	1420
60	1500	1785	1520	36	42	1700	1658	1520
	1600	1915	1620	40	48	1820	1775	1620
	1800	2115	1820	44	48	2020	1972	1820
	2000	2325	2020	48	48	2230	2182	2020



The company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company